

Appln No. 09/930,000

Amdt date October 25, 2004

Reply to Office action of July 26, 2004

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An electronic circuit prototyping system, comprising:

- a) a personal computer having at least one expansion slot;
- b) a multi-purpose data acquisition card installed in said expansion slot;

- c) software associated with said data acquisition card residing in memory of said personal computer and being in communication with said data acquisition card, said software including a custom communication driver; and

- d) a ~~prototyping~~ board interface coupled to said data acquisition card for connecting to a circuit to be tested, said ~~prototyping~~ board interface including

- i) a communication module for communicating with said data acquisition card and said associated software via said custom communication driver,

- ii) a function generator interface and variable DC voltage module coupled to said communication module,

- iii) a function generator module coupled to said function generator interface and variable DC voltage module,

- iv) an analog I/O module coupled to said communication module and to said function generator interface and variable DC voltage module,

- v) a current amplifier and frequency calibration

Appln No. 09/930,000

Amdt date October 25, 2004

Reply to Office action of July 26, 2004

module coupled to said communication module, to said function generator module, and to said analog I/O module, and

vi) a first edge connector for receiving one of a prototyping board and a protection board, said first edge connector being coupled to said communication module, to said function generator interface and variable DC voltage module, to said function generator module, to said analog I/O module, and to said current amplifier and frequency calibration module.

2. (Original) The system according to claim 1, wherein:

said communications module supports 8-bit write, 7-bit addressing, 1-bit parity checking, and 8-bit read.

3. (Original) The system according to claim 2, wherein:

said communications module has a data transfer rate of approximately 2400 bps.

4. (Original) The system according to claim 3, wherein:

said function generator module utilizes inexpensive digital to analog converters and analog switching gates to control a low cost analog function generator chip.

5. (Original) The system according to claim 4, wherein:

said digital to analog converters and analog switching gates are latched, so that said function generator can hold its state indefinitely.

6. (Original) The system according to claim 5, wherein:

Appln No. 09/930,000

Amdt date October 25, 2004

Reply to Office action of July 26, 2004

said function generator can generate sine, triangle and square waveforms from approximately 0.1 Hz to 250 kHz.

7. (Original) The system according to claim 6, wherein:

 waveform choice, coarse frequency, fine frequency, amplitude, and direct current (DC) voltage offset are all programmable.

8. (Original) The system according to claim 7, wherein:

 said function generator has amplitude modulation (AM) and frequency modulation (FM) inputs coupled to said first edge connector and to said analog I/O module.

9. (Original) The system according to claim 8, wherein:

 waveform output is fed back into said data acquisition card via analog gates.

10. (Original) The system according to claim 9, wherein:

 said analog I/O module includes analog gates and simple linear circuits for routing analog inputs and analog outputs of said data acquisition card to emulate a full-featured digital multimeter.

11. (Currently Amended) The system according to claim 10, wherein:

 said analog I/O module functions as both a 2-terminal and 3-terminal I-V curve tracer capable of characterizing diodes and transistors.

Appln No. 09/930,000

Amdt date October 25, 2004

Reply to Office action of July 26, 2004

12. (Currently Amended) The system according to claim 11, wherein:

said ~~prototyping~~ board interface further includes
vii) a manual control module and front panel coupled to said communication module, to said function generator interface and variable DC module, to said function generator module, to said analog I/O module, and to said current amplifier and frequency calibration module.

13. (Original) The system according to claim 12, wherein:

said function generator can be controlled from said personal computer or from said manual control module and front panel.

14. (Currently Amended) The system according to claim 13, wherein:

said ~~prototyping~~ board interface further includes
viii) an address and status module coupled to said communication module, to said function generator interface and variable DC module, to said analog I/O module, to said current amplifier and frequency calibration module and to said first edge connector.

15. (Currently Amended) The system according to claim 14, wherein:

said ~~prototyping~~ board interface further includes
ix) a protection board installed in said first edge

Appln No. 09/930,000

Amdt date October 25, 2004

Reply to Office action of July 26, 2004

connector, said protection board having a second edge connector for receiving a prototyping board.

16. (Original) The system according to claim 15, wherein:

said protection board includes at least one fuse, at least one resistor network, and at least one diode network.